

MS-12D17-GXXX



直接形式

G-SWITCH P/N

G020=2.0mm

G030=3.0mm

G040=4.0mm



P.C.B LAYOUT



SCHEMATIC

G-Switch:

使用温度范围: -20~70℃

耐压: AC250V 50Hz 1min

额定负荷: DC 12V 0.5A

操作力: 200g±100gf

接触电阻: ≤0.05Ω

动作寿命: 10000次

绝缘电阻: ≥100MΩ

NO.	PART	NAME	MATERIAL	QTY	FUNCTION
4	MINI-12 CONTACT/SPRING	MINI-12/17mm	PA66	1	As PLATE/PLATING
5	MINI-12 COIL	PA66/1.5mm	WIRE	1	BLACK/As (IN) PLATING
6	MINI-12 COVER	1.5mm	ABS	1	PAINTING
7	MINI-12 BUSH	PA66/1.5mm	WIRE	1	WHITE/BLACK



RoHS
Compliant
2002/95/EC



Unless otherwise specified, Tolerance:
X.0 ±0.30
X.1 ±0.20
X.2 ±0.15
X.xxx ±0.10
Angles ±3°

G-Switch Electronic (HongKong) CO.,Ltd.

DESIGN 陈伟祺	DATE 2016.05.29	TITLE:
CHECKED	DATE	MS-12D17-GXXX
APPROVED	DATE	
http://www.dg-switch.com		REV.: X1 SCALE: 4:1 UNIT: mm
TEL: 0769-82388879		SIZE: A4 SHEET: 1/1